



### Stamina

100% recycled vulcanized flooring that can be adhered, loose laid, or interlocked. The non-porous surface makes it an ideal flooring product for use in hockey arenas, free weight/fitness facilities or anywhere that a tough, slip-resistant, easy-to-clean floor is required.



Custom logo cutting available

Technical Specifications		
Hardness Shore A	ASTM D2240	80
Wear Layer Thickness	ASTM F410	>.050 (Passes)
Static Load Resistance	ASTM F970	0.002 (Passes)
Resistance to Chemicals	ASTM F925	Good
Resistance to Heat	ASTM F1514	4.29 (Passes)
Abrasion Resistance	ASTM D3389	0.16 gr. (Passes)
Dimensional Stability	ASTM F2199	Across (Passes)
Critical Radiant Flux	ASTM E648-03	No Class
Co-efficient of Friction	ASTM C1028	>.80 dry >.64 wet
Moisture Absorption	ASTM D570	0.27%
Thickness	ASTM F386	Passes
Size	ASTM F2055	Passes
Squareness	ASTM F2055	Passes
Quality of Cut	ASTM F511	Passes
Qualifies for LEED Points		Yes
Anti-microbial/Anti-fungal Properties		Yes

Size Specifications						
Thickness	Square			Interlock		
	Dimension	Weight	Area	Dimension	Weight	Area
10mm (3/8")	48" x 72"	60 lbs.	24 sq.ft.	44.3" x 66.5"	56 lbs.	20.46 sq. ft.
				44.3" x 44.3"	45 lbs.	13.63 sq.ft.
				22.2" x 22.2"	9 lbs.	3.42 sq. ft.
12mm (1/2")	48" x 72"	70 lbs.	24 sq.ft.	44.3" x 66.5"	66 lbs.	20.46 sq. ft.
17mm* (3/4")	48" x 72"	100 lbs.	24 sq.ft.	44.3" x 66.5"	86 lbs.	20.46 sq. ft.

\* black only

Standard Colors				
100	110	120	130	190

Colors: **100** Black **110** Black with Red speckle **120** Black with Grey speckle **130** Black with Blue speckle

**190** Black with Earth speckle

Custom colors are available by special order

Finishes: Smooth top, textured bottom